



KBHR1260 12V 35W

(Edition Aug 2011)

- Positive and negative plates in lead-calcium tin alloy
- Superior energy density
- Operates at a low internal pressure.
- Gas Recombination
- Usable in any orientation
- A recognized component of UL

- Very high power output
- Application specific designs
- A couple Range from 13W to 890W per cell for 10' @ 1.60Vpc
- Six months shelf life at 20°C
- Design life 5 years

HR Series


High Rate Discharge

The new ?UJgY' <F series batteries are specially designed for applications where need high power output. By optimum design of battery grids and plate paste formula, the HR series can deliver up to 40% more power than KAISE ST series.

KAISE BATTERIES has more than 15 year's experience in the manufacturing of VRLA batteries.

KAISE is one of the biggest manufacturers of SLA (or VRLA) batteries in the world, the biggest one in Mainland China and the first in China to develop and commercialize the sealed lead-acid battery with brand name KAISE and has been at the forefront of battery technology from day one.

KAISE leads the world in innovative battery technology. Our global network of sales and service engineers, backed in turn by our agents and distributors, means that we are currently active in more than 100 countries.



Dimensions and Weight

	SI Units	English Units
Length	151mm	5.94inch
Width	52mm	2.05inch
Height	94mm	3.70inch
Total Height	99mm	3.90inch
Approx. Weight	2.18Kg	4.81lbs

Performance Characteristics

- Nominal Voltage 12V
- Number of cell 6
- Nominal Capacity 68°F(20°C)
10 min wattage @ 1.6V 35W/cell
- Nominal Capacity 77°F(25°C)
20 hour rate (0.30A, 10.5V) 6.00Ah
- Internal Resistance
Fully Charged battery 68°F(20°C) 21mOhms
- Self-Discharge
3% of capacity declined per month at 20°C(average)

- Operating Temperature Range
Discharge -20~60°C
Charge -10~60°C
Storage -20~60°C
- Max. Discharge Current 68°F(20°C) 90A(5s)
- Short Circuit Current 570A
- Charge Methods: Constant Voltage Charge 68°F(20°C)
Cycle use 2.30-2.35VPC
Maximum charging current 2.4A
Temperature compensation -30mV/°C
- Standby use 2.23-2.27VPC
Temperature compensation -20mV/°C



KBHR1260 12V 35W

Discharge Data

Constant Current Discharge Data (Amperes at 20°C)												
End Voltage Per cell / V	5min	10min	15min	20min	25min	30min	35min	40min	45min	50min	55min	60min
1.60	29.9	20.3	15.6	12.3	10.3	8.95	7.90	7.12	6.51	5.93	5.46	5.06
1.65	28.1	19.2	14.8	11.7	9.75	8.49	7.51	6.77	6.19	5.65	5.20	4.83
1.70	26.3	18.1	14.0	11.0	9.22	8.03	7.11	6.41	5.88	5.36	4.94	4.59
1.75	24.6	17.0	13.2	10.4	8.69	7.57	6.71	6.06	5.56	5.08	4.69	4.36
1.80	23.5	16.4	12.7	10.1	8.44	7.37	6.54	5.91	5.43	4.96	4.58	4.26

Constant Power Discharge Data (Watts per cell at 20°C)												
End Voltage Per cell / V	5min	10min	15min	20min	25min	30min	35min	40min	45min	50min	55min	60min
1.60	53.1	35.0	27.2	21.6	18.2	16.0	14.0	12.6	11.5	10.5	9.8	9.17
1.65	50.8	33.7	26.3	20.9	17.6	15.4	13.6	12.2	11.1	10.2	9.52	8.92
1.70	48.6	32.4	25.3	20.1	17.0	14.9	13.2	11.8	10.8	10.0	9.24	8.67
1.75	46.4	31.1	24.4	19.4	16.4	14.4	12.7	11.4	10.4	9.50	8.97	8.41
1.80	44.1	29.8	23.4	18.7	15.8	13.9	12.3	11.1	10.1	9.32	8.69	8.16

Performance Drawings

